



## EXPLOSION PROOF TUBE-LIGHT FITTING

### TECHNICAL SPECIFICATION

Type of Ex-Protection	EEx-d Type, IS/IEC60079-1:2007
Zone Classification	Zone 1 & Zone 2
Gas Group	IIA, IIB & IIC, T6 IS/IEC60079-0:2004
Ingress IP Protection	IP65 IS/IEC60529-1:2001
Material of contraction	Die Cast Aluminum Alloy Lm6
Paint	Epoxy Polyester Powder Coating
Earthling	Internal -01 No. External -02 Nos.
Cable Entry	02 Nos. for M20 ( 3/4" ET)
Hardware	Stainless Steel
Reflector	S. S. 304 Mirror Finish
Lamp Rating	2 x 36Watt, 220 volts AC
Ballast	2 X 36Watt 220 Volts AC Electronic Type
LED Lamp	Suitable for UPTO 80Watt 24V/240Volts, AC/DC

#### TRI-FLP ENGINEERS PVT. LTD.

11, 1st Floor, Popular Indl. Estate, Gokhale Compound,  
Raghuvir Nagar, Near Char Rasta, Dombivli East,  
Dist Thane 421201, Maharashtra, India.

Tel : +91 0251 2433393 / 2452001 / 2440071 / 2440081

Email : vikas@trimurtitriflp.com / triflp@gmail.com

Web : www.explosionproof.co.in

